

## Tolleranze corde O.Rings in Gomma

*Rubber O.Rings cross section tolerances*

### Tolleranze corde O. Rings in gomma secondo ISO 3601/1

*ISO 3601/1 Rubber O.Rings cross section tolerances*

| Corda - Cross Section | Toll. - Tolerances ± |
|-----------------------|----------------------|
| 1,8                   | 0,08                 |
| 2,65                  | 0,09                 |
| 3,55                  | 0,10                 |
| 5,3                   | 0,13                 |
| 7                     | 0,15                 |

### Tolleranze standard Gapi per corde O.Rings in gomma

*Rubber O. Rings cross section Gapi Std tolerances*

| CORDA | min  | max  | CORDA | min   | max   |
|-------|------|------|-------|-------|-------|
| 1,00  | 0,92 | 1,08 | 5,00  | 4,87  | 5,13  |
| 1,50  | 1,42 | 1,58 | 5,30  | 5,17  | 5,43  |
| 1,60  | 1,52 | 1,68 | 5,70  | 5,57  | 5,83  |
| 1,78  | 1,70 | 1,86 | 6,00  | 5,87  | 6,13  |
| 1,90  | 1,82 | 1,98 | 6,99  | 6,84  | 7,14  |
| 2,00  | 1,92 | 2,08 | 7,00  | 6,85  | 7,15  |
| 2,40  | 2,31 | 2,49 | 8,00  | 7,85  | 8,15  |
| 2,50  | 2,41 | 2,59 | 8,40  | 8,25  | 8,55  |
| 2,62  | 2,53 | 2,71 | 9,00  | 8,82  | 9,18  |
| 2,70  | 2,61 | 2,79 | 9,50  | 9,31  | 9,69  |
| 3,00  | 2,91 | 3,09 | 10,00 | 9,80  | 10,20 |
| 3,50  | 3,40 | 3,60 | 12,00 | 11,76 | 12,24 |
| 3,53  | 3,43 | 3,63 | 14,00 | 13,72 | 14,28 |
| 3,60  | 3,50 | 3,70 | 16,00 | 15,68 | 16,32 |
| 4,00  | 3,90 | 4,10 | 18,00 | 17,64 | 18,36 |
| 4,50  | 4,40 | 4,60 | 20,00 | 19,60 | 20,40 |

Responsabile Qualità  
Quality Manager

